

MOTOwi⁴

Motorola Point-to-Point Bridges – PTP 600 Series


**Motorola PTP 58600 Bridges
5.8 GHz Part Numbers**

BP5830BH-2AA Integrated
BP5830BHC-2AA Connectorised
BP5830BH15-2AA Integrated Lite
BP5830BHC15-2AA Connectorised Lite

**Motorola PTP 54600 Bridges
5.4 GHz Part Numbers**

BP5530BH-2AA Integrated
BP5530BHC-2AA Connectorised
BP5530BH15-2AA Integrated Lite
BP5530BHC15-2AA Connectorised Lite

Spectrum-Efficient, High-Availability Wireless Ethernet Bridges

The PTP 600 Series of point-to-point wireless Ethernet bridges bring together the speed and reliability of licensed wireless with the flexibility of the unlicensed space. Operating in the 5.8 and 5.4 GHz bands at Ethernet data rates up to 300 Mbps, the systems are designed for virtually any environment – non-line-of-sight, line-of-sight and high interference – where high throughput is a major requirement and/or single or dual E1/T1 capability is needed.

Through Motorola's unique combination of technologies, PTP 600 Series solutions enhance link performance in a variety of applications, including T1 replacement, Voice-over-IP, video surveillance, distance learning, telemedicine and high-speed backhaul.

The PTP 600 Series bridges are incorporated in Motorola's **MOTOwi⁴**™ portfolio of innovative wireless broadband solutions that create, complement and complete IP networks. Delivering IP coverage to virtually all spaces, the **MOTOwi⁴** portfolio includes Fixed Broadband, WiMAX, Mesh, and Broadband over Powerline solutions for private and public networks.

Technical Specifications for the MOTOROLA POINT-TO-POINT BRIDGES – 600 SERIES

| RADIO TECHNOLOGY | REMARKS |
|---|---|
| RF band | 5.725 GHz–5.850 GHz* 5.470 GHz–5.725 GHz* |
| Channel size | 30 MHz |
| Channel selection/dynamic frequency control | By <i>Intelligent</i> Dynamic Frequency Selection (<i>i</i> -DFS) or manual intervention; automatic selection on start-up and continual adaptation to avoid interference; 10 MHz step size for WiMAX compatibility |
| Transmit power control | Varies with modulation mode and settings from 0 dBm to 25 dBm |
| System gain | Integrated: Varies with modulation mode; up to 163 dB using 23.5 dBi integrated antenna ** Connectorised: Varies with modulation mode and antenna type** |
| Receiver sensitivity | Adaptive, varying between -91 dBm and -58 dBm |
| Modulation | Dynamic; adapting between BPSK single and 256 QAM dual |
| Error correction | FEC, ARQ |
| Duplex scheme | TDD ratio: Dynamic or Fixed; same or split frequency Tx/Rx |
| Antenna: type/gain/B/W | Integrated: Integrated flat plate 23 dBi / 7° Connectorised: Approved to operate with flat plate up to 28 dBi or parabolic dish up to 37.7 dBi; connected via 2 x N-type female |
| Range | Up to 200 km (124 miles)*** |
| Security and encryption | Proprietary scrambling mechanism; optional AES 128 and 256 Bit Encryption * <i>Regulatory conditions for RF bands should be confirmed prior to system purchase</i> ** <i>Gain and maximum transmit power may vary based on regulatory domain</i> *** <i>In all cases the range limit is set by the latest software release</i> |
| ETHERNET BRIDGING & E1/T1 | REMARKS |
| Protocol | IEEE 802.3 |
| User data throughput | Integrated and Connectorised: Dynamically variable up to 300 Mbps at the Ethernet (aggregate) Integrated and Connectorised Lite: Dynamically variable up to 150 Mbps at the Ethernet (aggregate) |
| Latency | <1 ms each direction typical |
| Interface | 10 / 100 / 1000 Base T (RJ-45) – auto MDI/MDIX, 1000 Base SX option |
| E1/T1 Interface | G703/G704 G823/G824 Integrated and Connectorised: Provides dual E1/T1 ports Integrated and Connectorised Lite: Provides a single E1/T1 port |
| MANAGEMENT & INSTALLATION | REMARKS |
| LED indicators | Power status, Ethernet link status and activity |
| System management | Web or SNMP using MIBII, WiMAX and private MIB |
| Installation | Built-in audio assistance for link optimisation |
| Connection | Distance between outdoor unit and primary network connection: up to 100 metres (330') |
| PHYSICAL | REMARKS |
| Dimensions | Integrated outdoor unit (ODU): Width 370 mm (14.5"), Height 370 mm (14.5"), Depth 95 mm (3.75") Connectorised ODU: Width 309 mm (12.2"), Height 309 mm (12.2"), Depth 105 mm (4.1") Powered indoor unit (PIDU Plus): 250 mm (9.75"), Height 40 mm (1.5"), Depth 80 mm (3") |
| Weight | Integrated ODU: 5.5 kg (12.1 lbs) including bracket Connectorised ODU: 4.3 kg (9.1 lbs) including bracket PIDU Plus: 864 g (1.9 lbs) |
| Wind speed | 242 kph (150 mph) |
| Power supply | Integrated with Indoor Unit |
| Power source | 90–240 VAC, 50–60 Hz / 36–60V DC; redundant powering configurations supported |
| Power consumption | 55 W max |
| ENVIRONMENTAL & REGULATORY | REMARKS |
| Operating temperature | -40° C (-40° F) to +60° C (+140° F), including solar radiation |
| Protection and safety | UL60950; IEC60950; EN60950; CSA-C22.2 No. 60950 |
| Radio | 5.8 GHz: FCC Part 15, sub-part C 15.247, Eire ComReg 03/42, UK Approval to IR2007 5.4 GHz: EN 301 893 |
| EMC | USA–FCC Part 15, Class B; Europe–EN 301 489-4 |



For more information about the Motorola Point-to-Point Solutions:

Outside of North America: +44 1364 655500

In North America: +1 877 515-0400

www.motorola.com/ptp